



EXOCOAT Clearview

General Information

EXOCOAT Clearview is a unique solvent based durable hydrophobic coating for automotive windscreens, building glass, ceramics and chrome sanitary.

EXOCOAT Clearview is a 1K solution meant for consumer use.

Preparation

EXOCOAT Clearview can be used as such.

Material used

The following materials and equipment can be used

- Polishing cloth or pad: polyester microfiber
- If a machine is used: rotating buffing machine (1000-3000rpm)



Application

Substrate

- Glass, smooth ceramics (tiles) or chrome based sanitary

Operating instructions

1. Make sure the surface is dry and free from contamination (dust, oil). If required clean with, for example IPA, ethyl acetate or mineral spirits. Do not use cleaning agents or detergents prior to the application of EXOCOAT Clearview
2. Pour a few drops on the wiping cloth. A quantity of 25ml/m² is recommended
3. Wipe on the surface with pressure making circular movements (buffing)
4. Note the wetting of the substrate to be seemingly difficult, which is normal
5. Continue buffing for 15 minutes when manually applied, 2-3 minutes in the case of a buffing machine
6. Wipe of excess product until a transparent layer is gotten
7. Repeat steps 2 to 6 (2x) in climate zones with more frequent rains

Curing conditions

- Temperature, between 10 and 30°C
- Cures in 15 min



The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control, we disclaim any liability, including for patent infringement, incurred in connection with the use of these products, data or suggestions.

Europe, Americas, Middle East
and Africa
Axcentive SARL
Chemin de Champouse
13320 Bouc Bel Air, France
+33 4 42 69 40 90

Asia, India and Australasia
Axcentive Asia Pte Ltd
13 Lorong 8 Toa Payoh,
#07-01 Braddell Tech Park
319261 Singapore
+65 6258 6338